



EUROSILEX ASTAR (061201)

SILICONATED WHITE EXTERIOR PRIMER



Definition: Acrylic copolymer emulsion binder based, siliconated, pigmented exterior primer with powerful adherence capability. It is safely used for priming of external mineral surfaces such as plaster, concrete, gas concrete, brick and previously painted external surfaces prior to application of topcoat, especially when silicone based topcoat is to be used. Forms perfect bridging between surface and topcoat and reduces paint consumption.

Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: $1,52 \pm 0,02$ g/ml
Solid volume content	: $\% 61 \pm 1$, by weight
Viscosity (23 \pm 2 °C)	: 125 ± 130 KU
Color	: White
Package	: Plastic container

Coverage

1 liter will prime 11-13 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water at % 10–20 in volume.

Application

Apply one coat with brush, roller or spray equipment. Surface should be clean, dry and free from dust. Glossy surfaces must be sanded for better adhesion. “Eurosillex Macun” should be used for puttying where necessary. If surface is new apply priming using “Eurosillex Astar “. If surface is weak, absorbent or dusty, use “Binder” prior to priming with “Eurosillex Astar”. Apply final coating after waiting minimum 6-8 hours after priming.

Drying Time

Under normal conditions (50% \pm 5 RH and 23 \pm 2 °C) hard dry in 6-8 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L – 2,5 L

Precautions

- “ Stir paint thoroughly in original container until desired consistency is reached.
- “ Apply when surface temperature is between +5 °C and +30 °C.
- “ Do not apply under strong wind or hot sun.
- “ Wait at least 4 weeks for plaster to dry before applying primer if surface is new.
- “ Protect the surface from rain during application and until the paint is hard dry.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S2 - Keep out of reach of children
- S25 - Avoid contact with eyes.
- S29 - Do not empty into drains.
- S46 - If swallowed, seek medical advice immediately and show this container or label.