

EUROWHITE (061104) MICA ADDED FULL MATTE CEILING PAINT

Definition: Acrylic copolymer emulsion binder based, mica added full matte ceiling paint. It is safely used for decorative purposes on interior ceilings. It has perfect covering capability, very good adherence and allows the wall surface to breathe.

Technical Specifications

Dry film appearance Density Solid volume content Viscosity (23±2 °C) Color Package : Full Matte, Opaque : 1,79 ± 0,02 g/ml : % 70 ± 1, by weight : 120 ± 5 KU : White : Plastic container

Coverage

1 kg Eurowhite will paint 7-9 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water up to 15-20% in weight.

Application

Apply two coats using brush, roller or spray equipment. Surface should be cleaned by removing all oil, grease, loose and peeling paint before application. Glossy surfaces must be sanded for better adhesion. If surface is new, prime with "Arakat Flat". Priming with "Binder" is recommended if surface is satin plaster, puttied, dusty, weak or absorbent.

Drying Time

Under normal conditions (50% \pm 5 RH and 23 \pm 2 °C) touch dry in 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging 17,5 kg – 10 kg – 3,5 kg

Precautions

" Stir paint thoroughly in original container until desired consistency is reached.

" Wait at least 4 weeks before applying if surface is new.

" Apply when surface temperature is between +5 $^\circ\text{C}$ and +30 $^\circ\text{C}.$

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 Keep out of reach of children.
- S 25 Avoid contact with eyes.
- S 29 Do not empty into drains.
- S 46 If swallowed, seek medical advice immediately and show this container or label.



