


# **BiNDER** (011200 ) SILICONATED TRANSPARENT CONCENTRATED INSULATING PRIMER



**Definition:** Acrylic copolymer emulsion binder based, concentrated, transparent, siliconated, unfilled, insulating primer. It is used for priming weak, dusty and absorbent interior or exterior surfaces such as plaster and satin plaster.

## Technical Specifications

Dry film appearance	: Transparent
Density	: $1,00 \pm 0,02$ g/ml
Solid volume content	: % $34 \pm 1$ , by weight
Viscosity ( $23 \pm 2$ °C)	: $95 \pm 5$ KU
Color	: Transparent
Package	: Plastic container

## Coverage

1 Liter will paint 50 - 60 m<sup>2</sup> single coat, depending on smoothness of surface. Surface test is recommended for more accurate estimation.

## Dilution

Dilute with water in ratio 1 to 7 in volume.

## Application

Apply single coats using brush, roller or spray equipment. Surface should be strong, clean, dry and free from dust. Prior to application, exterior surfaces should be puttied using "Eurosilex Macun", interior surfaces should be smoothed using satin plaster or interior putty.

## Drying Time

Under normal conditions ( $50\% \pm 5$  RH and  $23 \pm 2$  °C) hard dry in 8-10 hours.

## Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

## Packaging

15 L – 2,5 L – 0,75 L

## Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Do not use before diluting. Suggested ratio is 1 to 7 in volume.
- " Do not apply under strong wind or hot sun.
- " Wait at least 4 weeks for plaster to dry before applying primer if surface is new.
- " Protect the surface from rain during application and until the paint is hard dry.

## Risk Warnings

R 22 - Harmful if swallowed.

## Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical  
bulletin



Dilute with  
water



Clean the  
surface



Stir



Apply with brush, roller or  
paint sprayer



Avoid  
frost