



HYBRiD (011120)

ULTRA LUXURY EXTERIOR PAINT



Definition: Produced with hybrid technology and high UV resistant pigments, pure acrylic emulsion binder based, high quality silk matte exterior final coat perfect adherence and covering capability. It is safely used for protective or decorative purposes on exterior mineral surfaces such as plaster, concrete, gas concrete, brick or previously painted exterior surfaces of buildings.

Technical Specifications

Dry film appearance	: Silk Matte, Opaque
Density	: White: 1,26 ± 0,02 g/ml
Solid volume content	: % 48 ± 1, by weight
Viscosity (23±2 °C)	: 110 - 115 KU
Color	: White
Package	: Plastic container

Coverage

1 Liter will paint 10 -13 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water up to 10-20% in volume.

Application

Apply 2 coats using brush, roller or spray equipment. Surface should be strong, clean, dry and free of dust. "Eurosilex Macun" should be used for puttying where necessary. Glossy surfaces must be sanded for better adhesion. Prime using "Hybrid Astar" if surface is newly finished. If surface is weak, absorbent or dusty use of "Binder" is recommended prior to priming with "Hybrid Astar". Apply two coats after allowing minimum of 24 hours for primer to dry. Wait minimum 6 hours (under normal conditions) before applying the additional coat.

Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Do not apply under strong wind or hot sun.
- " Wait at least 4 weeks before applying if surface is new.
- " Exterior paint or pigments should not be used for colouring.
- " Protect the surface from rain during application and until the paint is hard dry.
- " Using product of same batch is recommended to ensure hue consistency.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost

Conforms with
TS 7847 standards.