



# EUROSILEX (061100)

## SILICONATED EXTERIOR PAINT



**Definition:** Acrylic copolymer emulsion binder based, siliconated, high quality, matte exterior final coat with UV resistance and nanotechnological pigments, enabling self-cleaning by means of sunlight and rain exposure. It is safely used for protective or decorative purposes on exterior mineral surfaces such as plaster, concrete, gas concrete, brick or previously painted surfaces.

### Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: White: 1,56 ± 0,02 g/ml
Solid volume content	: % 64 ± 1, by weight
Viscosity (23±2 °C)	: 125 ± 5 KU
Color	: See Color card
Package	: Plastic container

### Coverage

1 Liter will paint 9 -12 m<sup>2</sup> single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

### Dilution

Dilute with water up to 10-20% in volume.

### Application

Apply 2 coats using brush, roller or spray equipment. Surface should be strong, clean, dry and free of dust. "Eurosilex Macun" should be used for puttying where necessary. Glossy surfaces must be sanded for better adhesion. Prime using "Eurosilex Astar" if surface is newly finished. If surface is weak, absorbent or dusty use of "Binder" is recommended prior to priming with "Eurosilex Astar". Apply two coats after allowing minimum of 24 hours for primer to dry. Wait minimum 6 hours (under normal conditions) before applying the additional coat.

### Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry 1-2 hours, hard dry in 24 hours.

### Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

### Packaging

15 L – 2,5 L

### Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Do not apply under strong wind or hot sun.
- " Wait at least 4 weeks before applying if surface is new.
- " Protect the surface from rain during application and until the paint is hard dry.
- " Using product of same batch is recommended to ensure hue consistency.

### Risk Warnings

R 22 - Harmful if swallowed.

### Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical bulletin



Dilute with water



Clean the surface



Stir



Apply with brush, roller or paint sprayer



Avoid frost

Conforms with  
TS 7847 standards.