



# EUROTEX (061900)

## SILICONATED EXTERIOR COATING



**Definition:** Acrylic copolymer emulsion binder based, high quality, siliconated, matte, fine grain exterior coating with increased UV resistance achieved through use of pigments of the latest technology. It is safely used for protective or decorative purposes on exterior mineral surfaces such as plaster, concrete, gas concrete, brick or previously painted surfaces of buildings.

### Technical Specifications

Dry film appearance	: Matte, Texture, Opaque
Density	: $1,81 \pm 0,02$ g/ml
Solid volume content	: $\% 77 \pm 1$ , by weight
Viscosity (23±2 °C)	: 4000 - 10000 poise
Color	: See Color card
Package	: Plastic container

### Coverage

1 kg will paint 0,7 - 1,1 m<sup>2</sup> single coat, depending on smoothness of surface. Surface test is recommended for more accurate estimation.

### Dilution

Ready for use. Dilute with water up to maximum 5% in weight if necessary.

### Application

Apply single coat using roller (coral sponge, sheepskin etc.) to obtain desired grain effect. Surface should be strong, clean, dry and free of dust. "Eurosilex Macun" should be used for puttying where necessary. Glossy surfaces must be sanded for better adhesion. Prime using "Eurosilex Astar" if surface is newly finished. If surface is weak, absorbent or dusty use of "Binder" is recommended prior to priming with "Eurosilex Astar". Single layer of coating is applied after allowing minimum of 24 hours for primer to dry.

### Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) hard dry in 24 hours.

### Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

### Packaging

25 kg

### Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Do not apply under strong wind or hot sun.
- " Wait at least 4 weeks before applying if surface is new.
- " Protect the surface from rain during application and until the paint is hard dry.
- " Using product of same batch is recommended to ensure hue consistency.

### Risk Warnings

R 22 - Harmful if swallowed.

### Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical bulletin



Dilute with water



Clean the surface



Stir



Apply using roller.



Avoid frost

Conforms with  
TS 7847 standards.