



# EUROSİLEX MACUN (061301)

## ACRYLIC EXTERIOR PUTTY



**Definition:** Acrylic copolymer emulsion binder based putty with flexible texture for filling and smoothing exterior surfaces. It is safely used on all kinds of plaster, concrete, gas concrete, brick and previously painted walls or floors, filling minor cracks, holes and crevices and obtaining an even and smooth surface.

### Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: $1,81 \pm 0,02$ g/ml
Solid volume content	: $\% 77 \pm 1$ , by weight
Viscosity (23 $\pm$ 2 °C)	: Putty
Color	: White
Package	: Plastic container

### Coverage

1 kg "EuroSilex Macun" will putty 0,8 - 1,3 m<sup>2</sup>, depending on porosity and smoothness of surface. Surface test is recommended for more accurate estimation.

### Dilution

Ready for use.

### Application

Surface where exterior putty is to be applied must be strong, clean, dry and free of dust. If surface is new add %20 cement and mix with water until application viscosity is reached. Depending on condition of surface, apply 2 or 3 layers with spatula or flexible steel trowel. Apply sanding or rubbing with wet felt until surface is smooth. Putty must be used within one hour after mixing with cement. On absorbent surfaces like gas concrete apply "Binder" after diluting with water in ratio 1 to 7 in volume .

### Drying Time

Under normal conditions (50%  $\pm$  5 RH and 23  $\pm$  2 °C) hard dry in 24 hours.

### Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

### Packaging

25 kg – 4 kg

### Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Larger cracks and holes must be levelled with cement mixtures prior to application.
- " Remainder can be stored for future use by covering top with water and tightly closing the lid.
- " Do not apply under strong wind or hot sun.
- " Wait at least 4 weeks before applying if surface is new.
- " Protect the surface from rain during application and until the paint is hard dry.

### Risk Warnings

R 22 - Harmful if swallowed.

### Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical  
bulletin



Clean the  
surface



Stir



Apply Spatula  
or steel trowel



Avoid  
frost