



SONKAT MAT (012100)

LUXURY SYNTHETIC MATTE PAINT



Definition: Alkyd binder base, high quality, matte final coat used safely on interior and exterior surfaces of metal or wood; such as furniture, doors, steel constructions, marine vessels on surfaces not in contact with sea water, reservoirs, tanks etc. It is easily applied using a brush, avoiding brush traces and dripping.

Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: White: 1,55 ± 0,02 g/ml
Solid volume content	: % 79 ± 1, by weight
Viscosity (23±2 °C)	: 110 ± 5 KU
Flashing Point	: 42 °C
Color	: 2 colors (White, Black)
Package	: Metal container

Coverage

1 Liter will paint 12-15 m², depending on surface and application.

Dilution

Dilute with Synthetic Thinner up to 5-10% in volume.

Application

Apply 2 coats using brush, roller or spray equipment. Surface must be cleaned by removing grease, rust and loose and peeling paint. Use putty "İshakol Boya Macunu" where necessary. Prime using "İshakol Astar". After burning knots and washing wood resin using (cellulosic thinner), wooden surfaces must be saturated with "Dekor ". Previously painted wooden surfaces must be fine sanded, puttied and primed using "İshakol Astar". Metal surfaces must be free from grease, rust and dirt, puttied, sanded and primed using "Europax" before application of "İshakol Sonkat Mat".

Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry in 1-2 hours, dust dry 4-5 hours, hard dry in 24 hours.

Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L - 2,5 L - 0,75 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Priming is absolutely necessary on raw surfaces or surfaces needing repair.
- " To ensure adhesion of paint glossy surfaces must be sanded dull and primed prior to application.

Risk Warnings

- R 10 - Flammable.
- R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 3/7/9 - Keep container tightly closed in a cool, well-ventilated place.
- S 13 - Keep away from food, drink and animal feedingstuffs.
- S 16 - Keep away from sources of ignition - No smoking.
- S 23 - Do not breathe vapour/spray.
- S 24/25 - Avoid contact with eyes or skin.
- S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.
- S 51 - Use only in well-ventilated areas.
- S 56 - Dispose of this material and its container at hazardous or special waste collection point.



See technical
bulletin



Dilute to application
viscosity



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Keep lid
closed



Xn
HARMFUL



F
FLAMMABLE

Conforms with
TS 39 standards.