



# EUROPAX (062201)

## ANTICORROSIVE PRIMER



**Definition:** It is alkyd binder base, rust preventing primer used safely on interior and exterior metal surfaces of all sorts, railways, steel constructions, marine vessels, high-voltage cable posts etc.

### Technical Specifications

Dry film appearance	: Silky Matte, Opaque
Density	: 1,40 ± 0,02 g/ml
Solid volume content	: %76 ± 1, by weight
Viscosity (23±2 °C)	: 95 ± 5 KU
Flashing Point	: 42 °C
Color	: 3 Colors (Grey, Red, White)
Package	: Metal Container

### Coverage

1 Liter will prime 11-13 m<sup>2</sup>, depending on surface and application.

### Dilution

Dilute with Synthetic Thinner up to 5-10% in volume.

### Application

Apply with brush, roller or sprayer. In spite of its powerful covering capability, apply 2 coats on pre-prepared surface in order to ensure active protection. Raw (unpainted) metal surfaces where Europax is to be applied must be sanded; and grease or dirt must be cleaned using synthetic thinner.

### Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry in 3-5 hours, dust dry 6-8 hours, hard dry in 24 hours.

### Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

### Packaging

15 L - 2,5 L - 0,75 L

### Precautions

“ Stir paint thoroughly in original container until desired consistency is reached.

“ Apply when surface temperature is between +5 °C and +30 °C.

“ Applicatin of Europax must be carried out without delay after the cleaning of surface. Delay of application will lead to faster corosion.

“ For effective protection of surface 2 coats of Europax must be applied before final coat “Sonkat or Sonkat Mat”.

### Risk Warnings

R 10 - Flammable.

R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

### Safety Warnings

S 2 - Keep out of reach of children.

S 3/7/9 - Keep container tightly closed in a cool, well-ventilated place.

S 13 - Keep away from food, drink and animal feedingstuffs.

S 16 - Keep away from sources of ignition - No smoking.

S 23 - Do not breathe vapour/spray.

S 24/25 - Avoid contact with eyes or skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 46 - If swallowed, seek medical advice immediately and show this container or label.

S 51 - Use only in well-ventilated areas.

S 56 - Dispose of this material and its container at hazardous or special waste collection point.



See technical  
bulletin



Dilute to application  
viscosity



Clean the  
surface



Stir



Apply with brush, roller or  
paint sprayer



Keep lid  
closed



Xn  
HARMFUL



F  
FLAMMABLE

Conforms with  
TS 11651 standards.