



PREKAST YÜZEY ASTARI (012204)

SYNTHETIC PRIMER



Definition: Special synthetic recine based, matte, white solvent based primer. It is safely used on interior or exterior surfaces, primarily on precast cement surfaces as well as brick, concrete, gas concrete, putted surfaces, fiberglass added surfaces and new plaster prior to final coat, enabling increased adherence.

Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: 1,44 ± 0,02 g/ml
Solid volume content	: % 73 ± 1, by weight
Viscosity (23±2 °C)	: 90 ± 5 KU
Flashing Point	: 42 °C
Color	: White
Package	: Metal container

Coverage

1 Liter will prime 8-10 m², depending on surface and application.

Dilution

Ready for use. Dilute with Synthetic Thinner up to max. 5-10% in volume if necessary.

Application

Apply single coat using brush, roller or spray equipment. Surface should be cleaned by removing all oil, grease, loose and peeling paint and should be dry, clean and strong. Where necessary, surface should be smoothed with cement based material or "Eurosilex Macun" use and primed after surface is dry.

Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry in 2 hours, dust dry 4-6 hours, hard dry in 8-10 hours, ready for final coat in 24 hours.

Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Glossy surfaces must be sanded for better adhesion.
- " The Product is not applied directly on EPS

Risk Warnings

- R 10 - Flammable.
- R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 3/7/9 - Keep container tightly closed in a cool, well-ventilated place.
- S 13 - Keep away from food, drink and animal feedingstuffs.
- S 16 - Keep away from sources of ignition - No smoking.
- S 23 - Do not breathe vapour/spray.
- S 24/25 - Avoid contact with eyes or skin.
- S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.
- S 51 - Use only in well-ventilated areas.
- S 56 - Dispose of this material and its container at hazardous or special waste collection point.



See technical
bulletin



Dilute to application
viscosity



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Keep lid
closed