



DEKOR (012400)

MATTE TRANSPARENT WOOD PAINT



Definition: Alkyd binder base semi-matte synthetic wood paint with transparent pigments providing high penetration. Lengthens lifetime of wooden surfaces applied. It is easy to apply, dries fast and allows surface to breath. It is safely used on exterior and interior, old and new woodwork and furniture for decorative purposes. Does not have antimicrobial and impregnating properties.

Technical Specifications

Dry film appearance	: Matte, Transparent
Density	: 0,83 ± 0,02 g/ml
Solid volume content	: % 21 ± 1, by weight
Viscosity (23±2 °C)	: Fluid
Flashing Point	: 40 °C
Color	: See Color card
Package	: Metal container

Coverage

1 Liter will treat 14-20 m² single coat, depending on absorbency of surface.

Dilution

Ready for use.

Application

Apply fine sanding on previously varnished surfaces. Unpainted wooden surfaces should be prepared by burning knots and washing wood resin using cellulosic thinner. If exterior wooden surface has not been previously treated it must be impregnated by using a suitable product for protection from mold, fungi and woodworm attack. Apply 1-2 coats of "Dekor" without diluting, using brush, roller, sponge or cloth. After application of each coat, excessives which might be seen on the surface must be wiped off using a cloth or sponge.

Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry in 2-4 hours, dust dry 6-8 hours, hard dry in 24 hours. Additional coat can be applied after 10-12 hours.

Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L - 2,5 L - 0,75 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.

Risk Warnings

- R 10 - Flammable.
- R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 3/7/9 - Keep container tightly closed in a cool, well-ventilated place.
- S 13 - Keep away from food, drink and animal feedingstuffs.
- S 16 - Keep away from sources of ignition - No smoking.
- S 23 - Do not breathe vapour/spray.
- S 24/25 - Avoid contact with eyes or skin.
- S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.
- S 51 - Use only in well-ventilated areas.
- S 56 - Dispose of this material and its container at hazardous or special waste collection point.



See technical bulletin



Clean the surface



Ready for use



Stir



Apply with brush, roller or paint sprayer



Keep lid closed



Xn
HARMFUL



F
FLAMMABLE