

# **DEKOVER** (012402) SILK-GLOSS VARNISH

**Definition:** Alkyd binder base, synthetic, transparent protective and decorative final coat wood varnish supplying a satin finish. Provides water resistance by forming a film on the surface. Easily penetrates into wooden surface and provides protection from UV light. Priming before application and varnishing after application will not be needed. Provides resistance against all kinds of pests and blue fungus. It is safely used on exterior and interior, old and new woodwork and furniture for protective and decorative purposes. Does not have antimicrobial and impregnating properties.

## **Technical Specifications**

Dry film appearance Density Solid volume content Viscosity (23±2 °C) Flashing Point Color Package Silky Glossy, Transparent
0,91 ± 0,02 g/ml
% 45 ± 1, by weight
55 ± 5 KU
42 °C
See Color card
Metal container

#### Coverage

1 Liter will varnish 14-20 m<sup>2</sup> single coat, depending on absorbency of surface.

#### Dilution

Ready for use.

#### Application

Previously painted wooden surfaces must be sanded. Unpainted wooden surfaces should be prepared by burning knots and washing wood resin using cellulosic thinner. If exterior wooden surface has not been previously treated it must be impregnated by using a suitable product for protection from mold fungi and woodworm attack. Apply one coat of clear "Dekor" for surface saturation. Apply 1-2 coats of "Dekover" of your color choice using brush, roller or spray equipment. "Dekover" will give a satin finish, eliminating the need to use varnish.

## **Drying Time**

Under normal conditions (50%  $\pm$  5 RH and 23  $\pm$  2 °C) touch dry in 2-4 hours, dust dry 6-8 hours, hard dry in 24 hours. Additional coat can be applied after 10-12 hours.

#### Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

# Packaging

15 L - 2,5 L - 0,75 L

#### **Precautions**

" Stir paint thoroughly in original container until desired consistency is reached.

" Apply when surface temperature is between +5 °C and +30 °C.

#### **Risk Warnings**

R 10 - Flammable. R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

#### **Safety Warnings**

S 2 - Keep out of reach of children.

- S 3/7/9 Keep container tightly closed in a cool, well-ventilated place.
- S 13 Keep away from food, drink and animal feedingstuffs.
- S 16 Keep away from sources of ignition No smoking.
- S 23 Do not breathe vapour/spray.
- S 24/25 Avoid contact with eyes or skin.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 46 If swallowed, seek medical advice immediately and show this container or label.
- S 51 Use only in well-ventilated areas.
- S 56 Dispose of this material and its container at hazardous or special waste collection point.



