



CAM CiLA (012403)

SINGLE COMPONENT PARQUET VARNISH



Definition: Urethane alkyd binder base final coat parquet varnish with clear and glossy appearance providing excellent abrasion resistance, and resistance to weather conditions. It is safely used for protective purposes on heavy wear surface like staircases, parquet and other wood floorings, as well as for decorative purposes on furniture such as tables and wooden chairs.

Technical Specifications

Dry film appearance	: Glossy, Transparent
Density	: 0,90 ± 0,02 g/ml
Solid volume content	: % 50 ± 1, by weight
Viscosity (23±2 °C)	: 55 ± 5 KU
Flashing Point	: 42 °C
Color	: Transparent
Package	: Metal container

Coverage

1 Liter will varnish 14-20 m² single coat, depending on condition of surface.

Dilution

Do not dilute when applying with brush or roller. Dilute with Synthetic Thinner up to 10% in volume if spray device is to be used for application.

Application

Clean surface free from all kinds of dirt and soil. Sand previously varnished surfaces until the old paint is totally removed. Fill the cracks and gaps with sawdust and varnish mixture or "ishakol Boya Macunu". Sand smooth the after the putty is dry. Apply 2-3 coats of on the prepared area, using brush, roller or spray equipment, waiting for 10-12 hours between coats. Fine sanding is recommended for improved adhesion between coats and for a smoother surface. "Cam Cila" will acquire full physical and chemical resistance in 4 days after the application.

Drying Time

Under normal conditions (50% ± 5 RH and 23 ± 2 °C) touch dry in 2-4 hours, dust dry 6-8 hours, hard dry in 24 hours. Additional coat can be applied after 10-12 hours.

Storage

Should be stored for 5 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L - 2,5 L - 0,75 L

Precautions

" Stir paint thoroughly in original container until desired consistency is reached.

" Apply when surface temperature is between +5 °C and +30 °C.

" For optimal results, apply the amount needed in thin layers, waiting for the required drying time (10-12 hours) between coats and fine sanding.

Risk Warnings

R 10 - Flammable.

R 20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

Safety Warnings

S 2 - Keep out of reach of children.

S 3/7/9 - Keep container tightly closed in a cool, well-ventilated place.

S 13 - Keep away from food, drink and animal feedingstuffs.

S 16 - Keep away from sources of ignition - No smoking.

S 23 - Do not breathe vapour/spray.

S 24/25 - Avoid contact with eyes or skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 46 - If swallowed, seek medical advice immediately and show this container or label.

S 51 - Use only in well-ventilated areas.

S 56 - Dispose of this material and its container at hazardous or special waste collection point.



See technical
bulletin



Clean the
surface



Ready
for use



Stir



Apply with brush, roller or
paint sprayer



Keep lid
closed



Xn
HARMFUL



F
FLAMMABLE

Conforms with
TS 8693 standards.