

OTTOMAN TAVAN (041103)

CEILING PAINT



Definition: Acrylic copolymer emulsion binder based, mica added, full matte ceiling paint. It is safely used for decorative purposes on interior ceilings. It has perfect covering capability, very good adhesion and allows the wall surface to breathe.

Technical Specifications

Dry film appearance	: Full matte, Opaque
Density	: $1,80 \pm 0,02$ g/ml
Solid volume content	: % 72 ± 1 , by weight
Viscosity (23 ± 2 °C)	: 120 ± 5 KU
Color	: White
Package	: Plastic container

Coverage

1 kg will paint 7-9 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water up to 15-20% in weight.

Application

Apply two coats using brush, roller or spray equipment. Surface should be cleaned by removing all oil, grease, loose and peeling paint before application. Glossy surfaces must be sanded for better adhesion. If surface is new, prime with "Ottoman Örtücü Astar". Priming with "Ottoman Konsantre Astar" is recommended if surface is satin plaster, puttied, dusty, weak or absorbent.

Drying Time

Under normal conditions ($50\% \pm 5$ RH and 23 ± 2 °C) touch dry in 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

20 kg

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Wait at least 4 weeks before applying if surface is new.
- " Apply when surface temperature is between +5 °C and +30 °C.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost

Conforms with
TS 5808 standards.