



OTTOMAN ÖRTÜCÜ ASTAR (041203)

WHITE INTERIOR PRIMER



Definition: Acrylic copolymer emulsion binder based, pigmented, white interior primer with high adherence capability. It is safely used as a primer on all kinds of mineral surfaces such as new plaster, concrete, gas concrete and brick prior to application of final coat. It forms a strong bridge between the surface and the final coat, reducing final coat consumption.

Technical Specifications

Dry film appearance	: Matte, Opaque
Density	: $1,32 \pm 0,02$ g/ml
Solid volume content	: $\% 44 \pm 1$, by weight
Viscosity (23 \pm 2 °C)	: 115 ± 5 KU
Color	: White
Package	: Plastic container

Coverage

1 Liter will prime 10-12 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water at 10-20% in volume.

Application

Apply one coat with brush, roller or spray equipment. Surface should be strong, clean, dry and free from dust. Glossy surfaces must be sanded for better adhesion. If surface is satin plaster, weak, absorbent or dusty use of "Ottoman Konsantre Astar" is recommended prior to priming with "Ottoman Örtücü Astar". Apply finalcoat after waiting minimum 6-8 hours after priming.

Drying Time

Under normal conditions (50% \pm 5 RH and 23 \pm 2 °C) hard dry in 6-8 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Wait at least 4 weeks for plaster to dry before applying primer if surface is new.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S2 - Keep out of reach of children
- S25 - Avoid contact with eyes.
- S29 - Do not empty into drains.
- S46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost