

OTTOMAN KONSANTRE ASTAR (041202)

1/7 CONCENTRATED PRIMER

Definition: Acrylic copolymer emulsion binder based, unfilled, transparent, siliconated, concentrated interior and exterior primer. It is used for priming weak, dusty and absorbent interior or exterior surfaces such as plaster and satin plaster.



Technical Specifications

Dry film appearance	: Transparent
Density	: $1,00 \pm 0,02$ g/ml
Solid volume content	: % 31 ± 1 , by weight
Viscosity (23 \pm 2 °C)	: 95 ± 5 KU
Color	: Transparent
Package	: Plastic container

Coverage

1 Liter will paint 50-60 m² single coat, depending on smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water in ratio 1 to 7 volume.

Application

Apply single coats using brush, roller or spray equipment. Surface should be strong, clean, dry and free from dust. Surfaces should be using satin plaster or interior putty.

Drying Time

Under normal conditions (50% \pm 5 RH and 23 \pm 2 °C) hard dry in 8-10 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L

Precautions

- “ Stir paint thoroughly in original container until desired consistency is reached.
- “ Apply when surface temperature is between +5 °C and +30 °C.
- “ Do not apply under strong wind or hot sun.
- “ Wait at least 4 weeks for plaster to dry before applying primer if surface is new.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost