



LIFETIME (011117)

ULTRA LUXURY SEMI GLOSS PAINT



Definition: Pure acrylic emulsion binder based, washable and resistant to stains owing to its special formulation, semi gloss interior final coat with perfect covering capability. It is safely used on interior surfaces of plaster, concrete, gas concrete, plaster panel, previously painted surfaces.

Technical Specifications

Dry film appearance	: Semi Gloss, Opaque
Density	: White : $1,27 \pm 0,02$ g/ml
Solid volume content	: % 51 ± 1 , by weight
Viscosity (23 ± 2 °C)	: 115 - 120 KU
Color	: White
Package	: Plastic container

Coverage

1 Liter will paint 15-20 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water up to 10-15% in volume.

Application

Apply 2 coats using brush, roller or spray equipment. Surface should be cleaned by removing all oil, grease, loose and peeling paint before application. Satin plaster or interior putty should be used where necessary. Glossy surfaces must be sanded for better adhesion. Prime with "Arakat" if surface is previously painted with solvent based paint, water-based semi-gloss, satin paint or is newly finished. If surface is satin plaster, puttied, dusty, weak or absorbent use "Binder" prior to priming with "Arakat Flat".

Drying Time

Under normal conditions ($50\% \pm 5$ RH and 23 ± 2 °C) touch dry in 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L – 2,5 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " Wait at least 4 weeks before applying if surface is new.
- " Apply when surface temperature is between +5 °C and +30 °C.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost

Conforms with
TS 5808 standards.