

# PANEL KAPI BOYASI (011122)

## PANEL DOOR PAINT



**Definition:** Pure acrylic emulsion binder based, semi-gloss final coat with high coverage and adherence, formulated specifically for panel doors. It can be used on all kinds of interior or exterior wooden surfaces.

### Technical Specifications

Dry film appearance	: Semi Gloss, Opaque
Density	: White: $1,27 \pm 0,02$ g/ml
Solid volume content	: % $51 \pm 1$ , by weight
Viscosity ( $23 \pm 2$ °C)	: $95 \pm 5$ KU
Color	: White + 4 colours
Package	: Plastic container

### Coverage

1 Liter will paint 15-20 m<sup>2</sup> single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

### Dilution

Dilute with water up to 10-15% in volume.

### Application

Apply 2 coats using brush, roller or spray equipment. Surface should be cleaned by removing all oil, grease, loose and peeling paint before application. Panel doors should be sanded and freed from dust prior to application of 2 coats of paint.

### Drying Time

Under normal conditions ( $50\% \pm 5$  RH and  $23 \pm 2$  °C) touch dry in 1-2 hours, hard dry in 24 hours.

### Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

### Packaging

0,75 L – 2,5 L

### Precautions

- “ Stir paint thoroughly in original container until desired consistency is reached.
- “ Apply when surface temperature is between +5 and +30 C
- “ Using product of same batch is recommended to ensure hue consistency.

### Risk Warnings

R 22 - Harmful if swallowed.

### Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical  
bulletin



Dilute with  
water



Clean the  
surface



Stir



Apply with brush, roller or  
paint sprayer



Avoid  
frost