



SONKAT LUXE (011118)

LUXURY GLOSS PAINT



Definition: Acrylic emulsion based, glossy, durable final coat for use on interior and exterior surfaces for decorative and protective purposes. Being water based, it is odourless and environment friendly and can be used on all kinds of interior or exterior surfaces as an alternative to glossy synthetic paints, as well as on plaster, concrete, gas concrete, plaster panel or previously painted interior or exterior surfaces, inside buildings. It is washable, resistant to UV rays, durable, avoiding yellowing and cracking and has breathing, adherence and high covering capability.

Technical Specifications

Dry film appearance	: Gloss, Opaque
Density	: White: $1,21 \pm 0,02$ g/ml
Solid volume content	: % 47 ± 1 , by weight
Viscosity (23 ± 2 °C)	: 90 ± 5 KU
Color	: White
Package	: Plastic container

Coverage

1 Liter will paint 15-20 m² single coat, depending on absorbency and smoothness of surface. Surface test is recommended for more accurate estimation.

Dilution

Dilute with water up to 5% in volume.

Application

Apply 2 coats using brush, roller or spray equipment on surfaces of metal, wood, stucco and the like. Surface must be cleaned by removing grease, rust and loose and peeling paint. Where necessary, use suitable putty for the type of surface to be painted. Unpainted wooden surfaces should be prepared by burning knots and washing wood resin using cellulosic thinner. Previously painted wooden surfaces must be puttied, sanded and primed using "İshakol Astar". Metal surfaces must be free from grease, rust and dirt, sanded where needed and primed using "Europax". Paint should be applied after the surface is totally dry.

Drying Time

Under normal conditions ($50\% \pm 5$ RH and 23 ± 2 °C) touch dry in 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L - 2,5 L - 0,75 L

Precautions

- " Stir paint thoroughly in original container until desired consistency is reached.
- " On new stucco surface, wait at least 4 weeks for surface to dry.
- " Apply when surface temperature is between +5 °C and +30 °C.
- " Priming is absolutely necessary on raw surfaces or surfaces needing repair.
- " To ensure adhesion of paint, glossy surfaces must be sanded dull and primed prior to application.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

- S 2 - Keep out of reach of children.
- S 25 - Avoid contact with eyes.
- S 29 - Do not empty into drains.
- S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost

Conforms with
TS 5808 standards.