



SUSET (011108)

LIQUID PLASTIC INSULATION MATERIALS



Definition: Elastomeric acrylic copolymer binder based, matte and smooth insulating primer. It is safely used for insulating wide surfaced flat or slanted roofs with multipoint extension joints, garage or bungalow roofs, terrace and balcony insulation, roof gutters, basement walls and concrete, gas concrete, cement panel, wood and metal surfaces where insulation is needed.

Technical Specifications

Dry film appearance	: Semi Matte, Opaque
Density	: $1,37 \pm 0,02$ g/ml
Solid volume content	: % 66 ± 1 , by weight
Viscosity (23 ± 2 °C)	: 130 - 135 KU
Color	: White
Package	: Plastic container

Coverage

1 Liter will cover 2.5 - 3.5 m² for 2 coats on vertical surfaces

1 Liter will cover 1.4 - 2.0 m² for 3 coats on horizontal surfaces

Minimum 3 coats should be used on horizontal surfaces. Coverage may differ depending on the absorbancy and smoothness of the surface.

Dilution

It diluted 25% by volume in the first coat.

Application

Apply 2 coats on vertical, 3 coats on horizontal surfaces using brush, roller or spatula. Surface should be cleaned by removing all oil, grease, loose and peeling paint before application. Prime with one coat of "Binder" after puttying with "Eurosilex Macun" where necessary. "Suset" should be applied after stirring well, with a time gap of 10-12 hours between coats with strokes from different directions, obtaining a dry film of minimum 1 mm. Final layer should be applied with vertical strokes. Dilute with water up to 25% for first coat. Second coat should be applied after 10-12 hours, diluting with water up to 10% maximum. Apply 3rd coat without diluting after 10-12 hours of drying time if the surface is horizontal.

Drying Time

Under normal conditions ($50\% \pm 5$ RH and 23 ± 2 °C) touch dry in 1-2 hours, hard dry in 24 hours.

Storage

Should be stored for 3 years in unopened original packs, in cool and dry area, avoiding frost and direct sunlight.

Packaging

15 L

Precautions

" Stir paint thoroughly in original container until desired consistency is reached.

" Apply when surface temperature is between +5 °C and +30 °C.

Risk Warnings

R 22 - Harmful if swallowed.

Safety Warnings

S 2 - Keep out of reach of children.

S 25 - Avoid contact with eyes.

S 29 - Do not empty into drains.

S 46 - If swallowed, seek medical advice immediately and show this container or label.



See technical
bulletin



Dilute with
water



Clean the
surface



Stir



Apply with brush, roller or
paint sprayer



Avoid
frost